2023 CAN-AM DEFENDER 6X6 DPS HD10



PACKAGE HIGHLIGHTS

- Dynamic Power Steering (DPS™)
- 64 in. wide with Arched A-arm
- · 14 in. cast-aluminum wheels
- 27 in. XPS Trail King tyres

Tundra Green / HD10

ENGINE	HD10
Туре	82 hp/69 lb-ft, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high-airflow ventilation, and Electronic Drive Belt Protection Extra L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok [†] auto-locking front differential
Driving Assistance	Electronic Hill Descent Control, ECO™/ECO™ Off/Work modes
Power Steering	Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Arched double A-arm/11 in. (27.9 cm) travel
Front Shocks	Twin tube gas-charged shocks
Rear Suspension	Arched TTA with external sway bar/11 in. (27.9 cm) travel
Rear Shocks	Twin tube gas-charged shocks
TYRES & WHEELS	
Front Tyres	XPS Trail King 27 x 11 x 14 in.
Rear Tyres	XPS Trail King 27 x 11 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Cage	Profiled cage, ROPS approved	
Estimated Dry Weight	1,953 lb (886 kg)	
LxWxH	154.1 x 64 x 78 in. (391.5 x 162.5 x 198.1 cm)	
Wheelbase	115.5 in. (294 cm)	
Ground Clearance	13 in. (33 cm)	
Cargo Box Dimensions	72 x 54.5 x 10 in. (180.3 x 138.4 x 25.4 cm)	
Cargo Box Capacity	1,000 lb (454 kg)	
Tailgate Load Capacity	250 lb (113.4 kg)	
Storage Capacity	Total: 10.4 gal (39.5 L)	
Towing Capacity	3,000 lb (1,360.8 kg)	
Payload Capacity	1,700 lb (771 kg)	
Fuel Capacity	10.6 gal (40 L)	
Person Capacity	3	

FEATURES

Gauge	4.5 in. wide digital display
Battery	12 V (18 amp/h)
Magneto	650 W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 140 W, LED tail lights
Winch	N/A
Seat	VERSA-PRO bench seat with passenger seat flipping up Underside hooks
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper, HMWPE central skid plate
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	2 years / 15,000 km, whichever comes first
Service Intervals	200 hours / 12 months / 3000 km



